AIAA2017-4295 (pdf)



NATIONAL INSTITUTE OF AEROSPACE

Uses of Zero and Negative Volume Elements for Node-Centered Edge-Based Discretization

Hiro Nishikawa AlAA Computational Fluid Dynamics, June 8, 2017

The cro MILIGHT ONE TO THE

"Forbidden Capability"

It is often said that most great inventions begin as a crazy idea. But a crazy idea should be handled carefully. If you get too excited and drawn into the craziness, you'd be trapped and never be able to come back to the real world.

Dr. Hiro Nishikawa, a CFD researcher, encounters an unusual and 'amazing' capability of CFD, but people don't take it seriously. He struggles to prove that it is real and useful in an attempt to escape from the Twilight Zone.




1997

NATIONAL INSTITUTE OF AEROSPACE

Adaptive-grid scheme for Cauchy-Riemann system

Adaptive-grid scheme (Roe 1996):



Adaptive-grid scheme converged to a tangled mesh.

"Forbidden Capability"

Hard to believe




"You must fix the grid."
"There must be a bug in your code."

Geometrical Interpretation



Solution of a pair of PDEs (2D) = Surface in 4D space.

The method adjusts the nodes to better approximate the surface.



Residual = Error in aligning a triangle tangent to the surface.


"A Geometric Interpretation of Fluctuations" 1997 (available at cfdnotes.com)

So, it doesn't matter whether a triangle is inverted or not.

"Grids and Solutions from Residual Minimization", PhD Thesis 2001

2001: Good grid or Bad grid






A bad grid can be a good grid for a bad scheme.

"Grids and Solutions from Residual Minimization", PhD Thesis 2001

2001: Perfect Shock Capturing



Adaptive-grid scheme converged and captured a shock perfectly with zero-volume triangles.




"Grids and Solutions from Residual Minimization", PhD Thesis 2001

2014

High-Reynolds-number viscous flow over a bump



1.5



0.7

CFD on a tangled grid is real

Truth is that he is not alone: Many other CFD researchers have a similar experience. However...

No formal publications are found. He begins to understand why. A big question is unanswered:





2016: Finally, asked a Good Question

HOW IS IN LISE FILLS

CFD on 'bad' grid indicates robustness, but it is almost always possible to 'fix' the grid.

Unless a scheme is proved to work with zero/neg-volume elements, and the use of them brings advantages, it generates no interests.



Hiro began to make a move.

Edge-Based Discretization




NASA's FUN3D; Software Cradle's SC/Tetra; DLR Tau code, etc.

$$\operatorname{div} \mathbf{f} = 0 \quad - \quad \frac{1}{V_j} \sum_{k \in \{k_j\}} \phi_{jk} |\mathbf{n}_{jk}| = 0$$

Numerical flux at edge-midpoint

$$\phi_{jk} = \frac{1}{2} (\mathbf{f}_L + \mathbf{f}_R) \cdot \hat{\mathbf{n}}_{jk} - \frac{1}{2} |a_n| (u_R - u_L)$$

linearly extrapolated L and R states.



Edge-based formula is a special flux quadrature.

Facts about EB Scheme



2nd-order only on simplex(tria/tet)-element grids.

3rd-order with quadratic LSQ fits on simplex grids.

Theory: Nishikawa Liu, JCP2017

Two schemes:


- I. Conventional scheme: 2nd-order accurate.
- 2. Hyperbolic scheme: 3rd-order for advection.


We consider advection-diffusion and Burgers' equations only. Euler and NS schemes will be considered in future.

Assumption on Grids



It can be mapped to a grid of all positive volumes.





Topologically equivalent.

Two Grid Metrics for EB



All computed such that an element has a positive volume when its nodes are ordered counterclockwise.


1. Directed area vector (per edge).

$$\mathbf{n}_{jk} = \mathbf{n}_{jk}^{\ell} + \mathbf{n}_{jk}^{r}$$

2. Dual volume (per node)

Sum of the contributions from surrounding elements (triangles).


-> Signed volume: negative or positive



Do NOT modify existing codes.

Directed Area Vector





Face normal may be inverted, but OK, so that


$$\sum_{k \in \{k_j\}} \mathbf{n}_{jk} = 0,$$

Do not even check the local direction of njk.

Dual Control Volume



Dual volume is independent of the location of j.



Keep zero/negative-volume elements as they are, so that we maintain a consistency condition:

$$\sum V_j$$
 = Total volume of the domain

Negative Dual Volume



Linear advection: $\partial_x(au) + \partial_y(bu) = 0$

Positive Dual volume:

$$\sum_{k \in \{k_j\}} \boldsymbol{\phi}_{jk} |\mathbf{n}_{jk}| = \left[\partial_x (au) + \partial_y (bu) \right] |V_j| + TE$$

Negative Dual volume:

$$\sum_{k \in \{k_j\}} \phi_{jk} |\mathbf{n}_{jk}| = -\left[\partial_x(au) + \partial_y(bu)\right] |V_j| + TE,$$


We'll be solving the target PDE with a negative sign.

LSQ Gradients




LSQ gradients are independent of element orientation.

It works with zero/neg-volume.



Shock-Capturing





EB residual reduces to the Rankine-Hugoniot:

$$Res_j = (|\overline{a}_n|\Delta u - \Delta f_n) |\mathbf{n}_L + \mathbf{n}_R|,$$

Implicit Solver



Jacobian-Free Newton's method

$$\mathbf{U}_h^{n+1} = \mathbf{U}_h^n + \Delta \mathbf{U}_h \quad \frac{\partial \mathbf{Res}}{\partial \mathbf{U}_h} \Delta \mathbf{U}_h = -\mathbf{Res}(\mathbf{U}_h^n)$$


NOTE: There is no pseudo time term (CFL=infinity).

It converges in 10 iterations (max 17) for all test problems.

Accuracy Verification

Advection equation





Forbider Capability

Answers to "How can they be useful?"




- Subdivided quads
- Discontinuity capturing
- Singularity
- Hanging nodes
- Overset grid

Subdivide Quads into Triangles




Subdivide quads into triangles to achieve 3rd-order accuracy. Negative volume elements may be generated, but that's OK.



Discontinuity Capturing

NATIONAL INSTITUTE OF AEROSPACE


Burgers' equation




Singularity with Multiple Nodes Laplace' equation




Reentrant corner problem: 1st-order accuracy at best [Laasonen 1967].




the singularity.





Singularity with Multiple Nodes Laplace' equation





-1.5

-2

-2.5

-3

OF Grid S-I

Grid S-II

Grid S-III

Slope 1

Slope 2

-1.5

Log 10 (heff)


1st-order accuracy with a single node at origin (expected).


2nd-order accuracy is achieved with multiple nodes at origin.

Hanging Nodes



advection-diffusion equation





EB scheme directly applied. 3rd-order accuracy can be achieved.


Overset Grid into Single Grid




advection-diffusion equation

Connect overset grids to create a single grid.

- Simplification in coding
- Discrete conservation






Overset Grid into Single Grid



0.3

advection-diffusion equation



Forbider Capability

Hiro demonstrated the usefulness of zero/negative-volume elements, and successfully published a conference paper. However, his task is not complete: theory, unsteady, Euler/Navier-Stokes, etc. His conference paper could turn out to be recognized as a landmark paper in future.



recognized as a landmark paper in future, or could be forgotten and varied in the shadow of the Twilight Zone.